



UNCLASSIFIED


ESTIMATING THE ERROR IN SIMULATION PREDICTION OVER THE DESIGN SPACE (U)

Rachel Shinn

*Embry-Riddle Aeronautical University
Aerospace Engineering
Prescott, Arizona
shinnr@erau.edu*

François M. Hemez, Scott W. Doebling

*Los Alamos National Laboratory
Engineering Sciences and Applications (ESA-WR)
Los Alamos, New Mexico
hemez@lanl.gov, doebling@lanl.gov*



Approved for unlimited release on August 27, 2002. LA-UR-02-5200. Unclassified.

WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED





UNCLASSIFIED

Abstract

Estimating the Error in Simulation Prediction Over the Design Space (U)

This study addresses the assessment of accuracy of simulation predictions. A procedure is developed to validate a simple non-linear model defined to capture the hardening behavior of a foam material subjected to a short-duration transient impact. Validation means that the predictive accuracy of the model must be established, not just in the vicinity of a single testing condition, but for all settings or configurations of the system. The notion of validation domain is introduced to designate the design region where the model's predictive accuracy is appropriate for the application of interest. Techniques brought to bear to assess the model's predictive accuracy include test-analysis correlation, calibration, bootstrapping and sampling for uncertainty propagation and metamodeling. The model's predictive accuracy is established by training a metamodel of prediction error. The prediction error is not assumed to be systematic. Instead, it depends on which configuration of the system is analyzed. The study shows how predictive accuracy can be assessed even in the presence of a calibrated model by calibrating to one point in the design space, then assessing with respect to experimental data elsewhere in the design space. Finally, the prediction error's confidence bounds are estimated by propagating the uncertainty associated with specific modeling assumptions.

Approved for unlimited release on August 27, 2002. LA-UR-02-5200. Unclassified.



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED





UNCLASSIFIED

Motivation

- The motivation of this work is the development of tools for Verification and Validation (V&V) because our objective is to make decisions based on *validated* simulations.
- A key component of V&V is the assessment of predictive accuracy.
- Example: Bill Press is asking us to demonstrate that our “science-based predictions” are *credible*.
- Example: What are the benefits in terms of improving the confidence in our simulations of performing another test?



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED







UNCLASSIFIED

Illustration

- What do we mean by “assessing the predictive accuracy” of a numerical simulation?

Error in the prediction of y



“For the setting of $p=3$, we can predict y with an expected accuracy of 7% +/- 1%, at the significance level of 96%.”

- Prediction accuracy includes the assessment of the sources of uncertainty and *lack-of-knowledge*.



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED





UNCLASSIFIED


Why Do We Make Assumptions?

- Assumptions enable model-building.


Reality of Interest



Conceptual Model



Computational Model



(From Collins, Hasselman & al.,
AIAA Journal, 1974.)

- Modeling assumptions *reduce* the uncertainty! It may result into a false sense of confidence in the predictions.
- The extent to which modeling assumptions influence the predictions and decisions must be quantified.



WEAPON RESPONSE (ESA-WR)


UNCLASSIFIED





UNCLASSIFIED

The First Step is the Definition of the Domain of Validation



- Prediction errors must be estimated through the design space, including in regions where physical experiments are *not* available.



WEAPON RESPONSE (ESA-WR)


UNCLASSIFIED





UNCLASSIFIED

The Second Step is the Assessment of Uncertainty From Modeling Assumptions



- The uncertainty introduced by the modeling assumptions (or *modeling error*) must be assessed and quantified.



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED







UNCLASSIFIED

Hyper-foam Impact Experiments

- Physical experiments are performed to study the propagation of an impact through an assembly of metallic and crushable (foam pad) components.



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED








UNCLASSIFIED

Configurations Tested

- Several configurations of the system are tested by varying the foam pad thickness (h) and drop height (d).



	Low Drop ($d=13''$, 0.3 m)	High Drop ($d=155''$, 4.0 m)
Thin Layer ($h=0.25''$, 6.3 mm)	10 Replicates	5 Replicates
Thick Layer ($h=0.50''$, 12.6 mm)	10 Replicates	5 Replicates



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED








UNCLASSIFIED

The Domain of Validation

- The crushing behavior of the foam material is represented by a 1D strain-stress constitutive equation.

$$F(x(t)) = k_{nl} (x(t))^q$$

- “How good is this model over this range of operating conditions?”



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED







UNCLASSIFIED

Response Features

- The response features of interest are the peak acceleration (*PAC*) and the time-of-arrival (*TOA*) at output sensor 2.



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED








UNCLASSIFIED

Single Degree of Freedom Modeling

- A single degree-of-freedom (SDOF) oscillator is developed to predict the features *PAC* and *TOA* without describing the crushable foam and dynamics with high-fidelity.



$$F(x(t)) = k_{nl} (x(t))^q$$



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED








UNCLASSIFIED

Dimensionality

- The dimensionality of the problem remains 2D, no matter which numerical simulation is implemented.



Variable	Description
1	Foam Thickness (inch)
2	Drop Height (inch)
3	Damping (lbf sec/inch)
4	Stiffness (lbf/inch ⁴)
5	Exponent (unitless)



Variable	Description
1	Foam Thickness (inch)
2	Drop Height (inch)
3	Tilt Angle 1 (degree)
4	Tilt Angle 2 (degree)
5	Bolt Preload (psi)
6	Stress Scaling (unitless)
7	Strain Scaling (unitless)
8	Input Scaling (unitless)
9	Friction (unitless)
10	Bulk Viscosity (unitless)



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED







UNCLASSIFIED

Calibration

- Material model parameters are calibrated by optimizing a multivariate T-test statistics of test-analysis correlation.



Calibrated Strain-stress Curve



Post-calibration Correlation



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED







UNCLASSIFIED

Prediction Errors Are Estimated at Discrete Locations in the Design Space

- The material model $F = k_{nl}x^q$ is calibrated w.r.t. settings ($h=1/4''$; $d=13''$), then used to predict other configurations.



Prediction of *PAC* Features



Prediction of *TOA* Features



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED





UNCLASSIFIED

Prediction Errors Are Extrapolated Throughout the Design Space





- The prediction errors are extrapolated over the design space using a family of polynomial metamodels.

- Definition of prediction errors:

$$e(h;d) = \left(y^{\text{Test}} - y(h;d) \right)^T S_{yy}^{-1} \left(y^{\text{Test}} - y(h;d) \right)$$

- Family of metamodels:

$$\left\{ \begin{array}{l} e(h;d) = c_1 + c_2 h + c_3 d \\ e(h;d) = c_1 + c_2 h + c_3 d + c_4 h d \\ e(h;d) = c_1 + c_2 h + c_3 d + c_4 h d + c_5 h^2 + c_6 d^2 \\ e(h;d) = c_1 + c_2 h + c_3 d + c_4 h d + c_5 h^2 + c_6 d^2 \\ \quad + c_7 d h^2 + c_8 h d^2 + c_9 h^3 + c_{10} d^3 \end{array} \right.$$



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED





UNCLASSIFIED

Criticism

- Calibration can be useful, but it generally does not assess whether a numerical model can be used with *confidence*.
- Experimental variability has not been accounted for.
- The functional form of the prediction error metamodels has been assumed ...
- ... So are the material model, initial condition, physical modeling, parameter calibration values, and loading.
- The effect of these assumptions must be quantified.



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED






UNCLASSIFIED

Effect of Experimental Variability


- The data features y^{Test} are bootstrapped from the available replicate impact tests for each configuration ($h;d$).



PAC Error Metamodel **TOA Error Metamodel**

$$e(h;d) = c_1 + c_2h + c_3d + c_4hd$$

Bilinear Error Metamodel



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED





Varying the Modeling Assumptions

- Instead of neglecting a potential *lack-of-knowledge* about the form of the error metamodel, such uncertainty is represented, using probabilities here.


Define Possible Alternatives

<p>“The model is linear.” $e(h;d) = c_1 + c_2h + c_3d$</p>
<p>“The model is bilinear.” $e(h;d) = c_1 + c_2h + c_3d + c_4hd$</p>
<p>“The model is quadratic.” $e(h;d) = c_1 + c_2h + c_3d + c_4hd + c_5h^2 + c_6d^2$</p>
<p>“The model is cubic.” $e(h;d) = c_1 + c_2h + c_3d + c_4hd + c_5h^2 + c_6d^2 + c_7dh^2 + c_8hd^2 + c_9h^3 + c_{10}d^3$</p>

Assign a Probability

Assumption	Probability
Linear	1.5%
Bilinear	42.2%
Quadratic	42.2%
Cubic	14.1%

Sample a Probability Law to Propagate the Uncertainty





UNCLASSIFIED

Prior and Posterior Probabilities

- The Bayes Theorem is used to assign probabilities, based on *prior* information and *likelihood* of each assumption.

Posteriors


$$\Pr(p | y^{\text{Test}}) = \frac{L(y^{\text{Test}} | p) \Pr(p)}{\int_{p \in \Omega} L(y^{\text{Test}} | p) \Pr(p)}$$

Priors (May come from past experience, legacy data, expert judgment).

Likelihood function (“goodness-of-fit” of each model).

$$L(y^{\text{Test}} | p) = ke^{-\frac{1}{2}(y^{\text{Test}} - y(p))^T S_{yy}^{-1} (y^{\text{Test}} - y(p))}$$

Assumption	Priors	Likelihood	Posteriors
Linear	30%	$4.59 \cdot 10^{-5}$	1.5%
Bilinear	30%	$1.28 \cdot 10^{-3}$	42.2%
Quadratic	30%	$1.28 \cdot 10^{-3}$	42.2%
Cubic	10%	$1.28 \cdot 10^{-3}$	14.1%



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED






UNCLASSIFIED

Propagation of Modeling Uncertainty

- Sampling the posterior probability law provides a family of error metamodels (1,000 Monte Carlo simulation).



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED









UNCLASSIFIED

Confidence Intervals of Accuracy

- The confidence intervals express the effect that modeling uncertainty has on the expected prediction accuracy.



“Necking” where physical tests are performed.

- Away from the physical tests, the prediction accuracy does not necessarily deteriorate ... but the uncertainty of the predictive assessment tends to grow.



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED





UNCLASSIFIED

Conclusion

- The concept of prediction accuracy is demonstrated with a simple model, a single source of experimental variability, and a single source of modeling uncertainty.
- The assessment of prediction accuracy is a pre-requisite to questions such as ...
 - What is the benefit of another physical experiment?
 - Which model is the best one for a particular application?
- A calibrated model can still be used for making predictions elsewhere in the design space ... as long as the prediction accuracy can be quantified.
- Extension to non-probabilistic approaches is considered.



WEAPON RESPONSE (ESA-WR)

UNCLASSIFIED

